## **Permeable Pavement**

## Definition/Purpose

Permeable pavement is an alternative to conventional concrete and asphalt paving materials that allows rapid infiltration of stormwater. Stormwater infiltrates into a porous paving material that provides tem porary storage until the water infiltrates into underlying permeable soils or through an underground dra in system. This practice is intended to reduce stormwater runoff rate and volume, as well as associated pollutants transported from the site by stormwater runoff.

## **Policies**

Practice must be combined with impervious surface removal. Surface area of permeable pavement to be cost-shared shall not exceed the portion of impervious surface removed.

- The soils beneath the permeable pavement must have sufficient infiltration capacity for the per meable pavement to drain.
- 2. The site must be located in the Sand Hills or Coastal Plains physiographic regions, including all ba rrier islands (refer to the map on following page). An exception to this requirement can be mad e on a case by case basis for sites in other areas of the state if soil within a one-mile radius of the site is classified as coarser than loamy very fine sand for the top three feet asdefined by the USDA NRCS.
- Permeable pavement shall not be installed until the upslope and adjoining areas are stabilized.
  After installation, barriers shall be installed to prevent construction traffic from driving on the pavement.

Practice should be sited away from construction or other activities that can produce sediment-laden runoff. Soil clogs permeable pavement, making it ineffective.

**Formatted:** Normal, Indent: Left: 0.25", No bullets or numbering

The practice must be installed and maintained in accordance with the Division of Energy,
 Mining, and Land Resources standards and specifications (link here:
 http://portal.ncdenr.org/web/wq/ws/su/bmp-ch18)

Formatted: Indent: Left: 0.5", No bullets or numbering

Formatted: Normal, No bullets or numbering

3.

4. -The practice must have the Design Form Supplement completed as a part of the design for this practice

Formatted: Normal, Indent: Left: 0.25", No bullets or numbering

4.5. Practice must be installed and maintained in accordance with manufacturer's specifications.

5.6. An operation and maintenance plan for the site must be developed and implemented.